

TKST 21

SKF Stethoscope

Simple method to 'hear' bearing and machine noise

The TKST 21 captures acoustic data from bearings and other rotating parts – in order to prevent machine failure.

It includes a headset and two probes – 70 mm and 300 mm in length – in a sturdy carrying case. Pre-recorded audio samples of the most common problematic bearing noises are available in the device. The audio samples allow reliable identification of the possible cause of the noise. These sounds are also available on SKF.com.

The sound examples include: an undamaged bearing; a damaged inner ring; a less-damaged inner ring; a damaged outer ring; a damaged ball; and contamination by ashes and cavitation.

Noise from rotating machinery is picked up by a stick probe and transmitted to a sensor. This converts into an electrical signal, which is processed and amplified. The amplified signal can be fed to the headset, or to a recorder. Volume is easily adjusted to a comfortable level; the TKST 21 stethoscope can even be muted when needed. The headset is also an approved ear defender.

The device can detect a wide variety of typical problems, such as:


- Damaged bearings
- Valve chatter
- Tappet noise
- Piston slap
- Gear and pump noise

Online sound examples of an undamaged bearing, damaged inner ring, less damaged inner ring, damaged outer ring, damaged ball, contamination by ashes and cavitation.



Advantages of the TKST 21 include:

- Large, backlit colour display
 - User friendliness and easy one-hand operation
 - Lightweight and ergonomic design
 - Off-line and online pre-recorded demonstration samples
 - High quality, noise cancelling headset
 - Easily adjustable volume control
- Frequency range of 30 Hz-15 kHz



Handheld instrument for monitoring bearing and machine noise to prevent machine failure

With a large, backlit colour display, a unique feature for this type of device, the TKST 21 is very user friendly. Operators can listen in 'live' mode, or record sounds. These recorded sounds can be replayed and compared with the live sound.

Features of the Settings menu include: changing the display brightness; auto-off timing; turning the SKF library of sound samples ON or OFF; and switching the volume limiter OFF.

The device can be used to detect noise in machine components – including bearing housings, gears, valves, vents and pumps. By monitoring noise, it can help to detect errors at an early stage – to enhance maintenance and help avoid failure.

The TKST 21 can be applied in a variety of industries, including:

- Power plants
- Recycling facilities
- Automotive factories
- Materials handling
- Food/beverage facilities
- Paper mills
- Gear and pump noise



Technical data			
Designation	TKST 21		
Frequency range	30 Hz– 15 kHz	Dimensions handset	230 x 70 x 38 mm (9 x 2.8 x 1.5 in)
Operating temperature	-10 to +45 °C (14 to 113 °F)	Probe length	70 and 300 mm (2.8 and 11.8 in.)
Output volume	Adjustable in 10 levels	Case dimensions	360 x 110 x 260 mm (14.2 x 4.3 x 10.2 in.)
LCD	Color backlit TFT	Weight	
Sound volume	Up, down and mute	Total	1670 g (3.68 lb)
Battery low signal	Yes	Instrument	290 g (0.64 lb)
Menus and features	Live, Recording, Sounds samples, Settings	Headset	290 g (0.64 lb)
Maximum recorder output	250 mV	Case contents	1 x Instrument
Headset	32 ohm (right and left merged)		1 x Headset
Auto switch off	After 5 or 10 min., or OFF		1 x Probe 70 mm (2.8 in.)
Battery	2 x AA Alkaline (included)		1 x Probe 300 mm (11.8 in.)
Battery lifetime	Minimum 10 hours (continuous use)		2 x AA Alkaline battery
			1 x Instructions for use

skf.com | skf.com/mapro | skf.com/lubrication

© SKF is a registered trademark of AB SKF (publ).

© SKF Group 2022. All rights reserved. Please note that this publication may not be copied or distributed, in whole or in part, unless prior written permission is granted.

Every care has been taken to ensure the accuracy of the information contained in this publication, but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 19495 EN · November 2022